



Insert Part Number		3520-42.00X1.5D
Insert Thread Form		Metric Coarse
Nominal Thread Size		M42 X 4.50
Insert Length Q (installed)	D	1.5D
Insert Length Q (installed)	mm	63.00
Insert Material		304 Stainless Steel
Insert Coating/Plating		-
Military Standard	#	
National Aerospace Standard	#	
Federal Stock	#	
National Stock / NATO	#	

Optimum thread performance with Wire Thread Inserts is achieved when the inserts are installed 1/2 to 1 pitch below the surface of the tapped hole. This means that the actual length of an installed insert is equal to dimension Q less 1/2 to 1 pitch. Dimensions S and T allow for tap end clearance of intermediate taps. When using Bottoming and Spiral Flute Taps these dimensions maybe reduced by an amount equal to 2 thread pitches. Any countersink depths must be added to these dimensions.

COMPATIBLE POWERCOIL INSTALLATION AND REMOVAL TOOLS	
TOOL TYPE	Part #
Hand Installation Tool	3500-HIT28
Tang Break Tool	-
Removal Tool	3500-RT4
Machine Installation Tool	-
Mandrel Installation Tool	-
Captive Prewinder Tool	-
Non-Captive Prewinder Tool	-
Spring Loaded tang Break Tool	-
Pneumatic Front end assembly (FEA)	-
FEA Mandrel	-
FEA Nozzle	-
Pneumatic Tool	-

powercoil.com.au

PowerCoil is a registered trademark of Bordo International Pty Ltd Australia



DRILLED HOLE DIMENSIONS INTERMEDIATE/PLUG TAP

Drill Size	mm	43.00
Drill Part Number		2608-43.00
Drill Size inch	inch	1.11/16
Drill Part Number inch		2607-1.11/16
A Minor Diameter inimum	mm	42.975
A Minor Diameter maximum	mm	43.505
S Drilling Depth minimum	mm	83.25

TAPPED HOLE DIMENSIONS

Tap Size	STI		M42 X 4.50
Tap Size	-		-
B Major Diameter		mm	47.846
C Pitch Diameter MIN		mm	44.923
C Pitch Diameter MAX	5H	mm	45.098
C Pitch Diameter MAX	6H	mm	45.147
T Tapping Depth MIN		mm	78.75
Power Coil Tap Part Number	STI	Taper	-
Power Coil Tap Part Number	STI	Intermediate	-
Power Coil Tap Part Number	STI	Bottoming	-
Power Coil Tap Part Number	STI	SpiralPoint	-
Power Coil Tap Part Number	STI	SpiralFlute	-

INSERT SPECIFICATIONS

E Fitted Minor Diameter	mm	37.129
Q Nominal Length Installed	mm	63.00
Free Coil Diameter minimum	mm	47.10
Free Coil Diameter maximum	mm	49.00
Free Coils minimum	#	11.80
Free Coils maximum	#	12.20



IMPORTANT The success of any drilling and tapping operation is dependant upon many factors -type of material being cut, cutting speed, coolant, equipment being used - and it is not possible to give specific drill sizes for each material. Drill sizes shown are recommendations only and PowerCoil would strongly suggest that independent testing be performed for specific and critical applications. When using wire thread inserts it is important that the drilling and tapping diameters and lengths shown are adhered to. The figures outlined in these tables encompass effective free coil tolerances for most globally recognized standards and manufacturers, including those of reduced diameter wire thread inserts.

Number of Free Coils – the number of coils on an un-installed insert counted along the insert length 90° from the tang.

